



Precoat Instructions for the 108.1012 Washable Filter Cartridge Kit

Prior To Initial Use

The cartridge filter has to be precoat with 2 cups of Precoat prior to initial use. The precoat should be fed into the pickup hood or slot. After precoating with the filter let the fan operate for two (2) minutes to allow the Precoat to settle on the inside of the filter.

After Initial Precoat

The suction will deteriorate as the filter loads up with particulate. When it is time to clean the filter you remove the filter, turn it upside down, blow it out on the outside with compressed air then attach it back to the fan and precoat the unit the same as the initial precoat instructions.

The filter can be cleaned with water, as the media does not retain any moisture. However, getting rid of the water and particulate could be a problem as people are concerned with dumping hazardous particulate down a drain. You can dispose of the particulate in a bag if the filter was cleaned with compressed air.

Date: July 21, 2009

Section 5
Page 1 of 2

IN U.S.A.
ENVIROFLEX INTERNATIONAL INC.
1051 CLINTON ST.
BUFFALO NY, USA 14206-2823
TEL. (716) 883-2319 FAX (716) 892-2139
TOLL FREE 1-866-ENV-FLEX
Internet: <http://www.enviroflex.com>
Email: Info@enviroflex.com

IN CANADA
ENVIROFLEX INTERNATIONAL INC.
17 BROWNRIIDGE RD. UNIT 8
HALTON HILLS, ONTARIO, CANADA, L7G 0C6
TEL. (905) 636-1177 FAX (905) 636-1178
TOLL FREE 1-877-ENV-FLEX
Internet: <http://www.enviroflex.com>
Email: info@enviroflex.com